

2. Specifications

VE TRANSFER SWITCH	COS 0 - 5kVA	COS 0 - 10kVA
Nominal voltage	200 - 250V AC, Single phase	
Nominal frequency	50 – 60 Hz	
Input 1, Nom. current	20 A	40 A
Input 2, Nom. current	20 A	40 A
Output, Nom. current	20 A	40 A
Max. motor (airco) power	1,3 kW	8 kW
Power consumption Input 1	6 VA	6 VA
Power consumption Input 2	0 VA	0 VA
Transfer time by closing contacts	10 – 20 msec.	10 – 20 msec.
Transfer time by opening contacts	5 – 20 msec.	5 – 20 msec.
Transfer time by closing contacts	10 – 20 msec.	10 – 20 msec.
Contacts delay Input 1	Approximately 10 sec. (adjustable)	
Auxiliary contact	200 - 240V AC; 20 A, cos φ =1	
GENERAL		
Operating temperature	-5°C to + 60°C	
Humidity (non-condensing)	Max. 95%	
Miniature circuit breaker (MCB)	Not included – installation dependent	
Earth leakage breakers (RCD)	Not included – installation dependent	
ENCLOSURE		
Protection category	IP 54	
Colour	RAL 7035	
Dimension h x w x d (mm)	175 x 215 x 120	175 x 215 x120
Weight (kg)		

